Version 2004.3.qxd 8/13/2004 4:36 PM Page 28

FAIRWAY COMPOSITE RAILING

Mechanical Property	PVC	Test Method
Flexural Strength, MOR psi.	6000	ASTM D 790
Flexural Modulus, E psi.	900,000	ASTM D 790
Compressive Strength Parallel, psi.	7400	ASTM D 143
Compressive E Parallel, psi.	890,000	ASTM D 4761
Compressive Strength Perpendicular, psi.	7100	ASTM D 143
Tensile Strength Parallel, psi.	2800	ASTM D 638
Tensile E Parallel, psi.	900,000	ASTM D 790
Shear Strength Parallel, psi	1300	ASTM D 143
Specific Gravity	1.12	ASTM D 2395
Self Ignition Temperature °F (°C)	761 (405)	ASTM D 1929
Flash Ignition Temperature °F (°C)	671 (355)	ASTM D 1929
Water Absorption % (24 hour soak)	1.2%	ASTM D 1037
Thickness Swell % (24 hour soak)	0.4%	ASTM D 1037
Biodeterioration: Decay Resistance	Equivalent or superior to preservative treated lumber	ASTM D 1413
Termite Resistance		ASTM D 3345
Marine Borer Resistance		ASTM D 2481

[1]Testing conducted by Professional Service Industries Inc. and Washington State University

FAIRWAY VINYL CLEANER MSDS

Manufactured By: **Product Name:** CITRUS SHINE

PRODUCTS CHEMICAL COMPANY 6400 Herman Av Cleveland OH 44102

EMERGENCY: phone number involving spill, leak, fire or accident: INFOTRAC 800-535-5053

MATERIAL SAFETY DATA *(Prepared According to 29CFR 1910,1200)*

SECTION 1 -- PRODUCT IDENTIFICATION

Product Code # 1521

PRODUCT NAME:

PRODUCT TYPE: ALL PURPOSE SPRAY CLEANER

COMPANY NAME:

COMPANY ADDRESS:

Proper Shipping Name: COMPOUND, CLEANING LIQUID, NOI

HMIS Rating Health ... 1 Fire ... 0 Reactivity ... 0 Personal Protection ... B

Formula Proprietary

Revision Date: 02/01

SECTION 2 -- INGREDIENTS

CHEMICAL NAME	CAS NO.	PERCENT WT	313 / CHEM	PEL	TWA-TLV	CARCINOGEN
WATER	7732-18-5	85 to 90	N			NO
POTASSIUM HYDROXIDE	1310-58-3	0 to 5	N	2	2	NO
SULFONIC ACID	27176-87-0	5 to 10	N			NO
2 BUTOXYETHANOL	111-76-2	3.522	Y	25	25	NO
CITRUS TERPENES	68647-72-3	0 to 5	N			NO
DYE	518-47-8					NO

This product contains materials subject to the reporting requirements of SARA, Section 313 Emergency Planning & Right-To-Know Act.

SECTION 3 -- PHYSICAL DATA

Boil Point 212
Vapor Press.(mmhg) 20@68f
VaporDensity (AIR=1) N/A
Solubility in Water: CMP
Appearance / Odor: GREEN LIQUID/CITRUS
Specific Gravity 1.02
Volatile: 95
pH 7.5
Evap. Rate (H2O=1) 1-1

SECTION 4 -- FIRE AND EXPLOSION DATA

Flash Point: N/A (TCP)
Flammable Limits: N/A
Extinguishing Media: Non-Flammable
Special Fire Fighting Procedures: N/A
Fire, Explosion Hazards: N/A

SECTION 5 -- REACTIVITY DATA

Stability: STABLE
Hazardous Polymerization: WILL NOT OCCUR
Incompatibility: NONE KNOWN
Hazardous Decomposition: NONE KNOWN

SECTION 6 -- STORAGE AND HANDLING

KEEP OUT OF THE REACH OF CHILDREN
For sale to, use & storage by trained persons only

SECTION 7 -- HEALTH AND FIRST AID

EYES: May Cause eye irritation.

SKIN: May cause skin irritation.

INHALATION:

INGESTION: May cause irritation to the intestine, mouth, throat, & esophagus.

EYES: Flush eyes with large amounts of water. Consult physician if irritation continues.

SKIN: Flush with water.

INHALATION: Move person to fresh air. Consult physician

INGESTION: Induce vomiting. Drink large quantities of water. Consult Physician.

SECTION 8 -- SPECIAL PROTECTION DATA

Repository Protection: Adequate ventilation
Ventilation as required to maintain TLV
Protective Gloves: Rubber Gloves Recommended.
Eye Protection: Safety Glasses Recommended

SECTION 9 -- SPILL OR LEAK PRECAUTIONS

Steps to be taken in case of spill or leak:
Mop or absorb for disposal
Waste disposal Method:
Sewer or incinerate with local approval.

N/A = Not Applicable CMP = Complete